

AUG 30 2002

## IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant: M. Loose

Examiner: C. Kao

Serial No. 09/671,409

Art Unit: 2882

Filing Date: September 27, 2000

For: IMAGER WITH ADJUSTABLE RESOLUTION

Assistant Commissioner for Patents  
Box Non-Fee Amendment  
Washington, D.C. 20231

AMENDMENT AFTER FINAL OFFICE ACTIONTRANSMITTAL

Sir:

Transmitted herewith is an amendment for this application. Applicant is a large entity.


Fee for Claims

	Claims Remaining After Amendment	Highest No. Previously Paid For	Present Extra	Rate	Addit. Fee
TOTAL	8	14	0	18.00	0.00
INDEP.	3	3	0	84.00	0.00

If any additional fee is required, charge Account No. 18-1750. A duplicate of this transmittal is attached.

Respectfully submitted,

August 30, 2002

  
Steven C. Patrick  
Registration No. 40,341  
Attorney for Applicant

KOPPEL, JACOBS, PATRICK & HEYBL  
555 St. Charles Drive, Suite 107  
Thousand Oaks, California, 91360  
Telephone: (805) 373-0060

M S2-00SC053US3amend trans

RECEIVED  
AUG 30 2002  
PATENT  
OFFICERECEIVED  
AUG 30 2002  
PATENT  
OFFICE

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant: M. Loose

Serial No. 09/671,409

Examiner: C. Kao

Filed: September 27, 2000

Art Unit: 2882

Title: IMAGER WITH ADJUSTABLE RESOLUTION

Assistant Commissioner for Patents

Box Non-Fee Amendment

Washington, D. C. 20231

AMENDMENT AFTER FINAL OFFICE ACTION

Sir:

In response to the Office Action dated July 19, 2002, kindly amend the above application as follows. Please note that, in accordance with 37 C.F.R. § 1.116, the present amendment only cancels claims and amends claims in compliance with requirements of form expressly set forth in the Examiner's previous Office action.

Claims

Please cancel claims 8 and 12.

Please amend claims 9, 13 and 15 as follows:

9. (amended) A photodetector array with selectable resolution, comprising:

a plurality of photodetectors;

a switching circuit which configures neighboring ones of said photodetectors into pixels by directly summing at each pixel the outputs of multiple photodetectors into an aggregated pixel output, said aggregated pixel output stored on said pixel's intrinsic capacitance prior to being read out;

wherein said switching circuit is electronically